JAEA Activities on Decontamination toward Environmental Restoration of Fukushima





JAEA Activities for Environment Restoration


- 1. Assessments of Radiological Contamination Situation
 - monitoring and mapping
- 2. Demonstration of Decontamination Measures
 - schoolyard and swimming pool
 - model projects for residential areas
- 3. R&D on Environmental Restoration
 - monitoring system using an AUH
 - computer simulation for dose reduction, etc.
- 4. Communication Activities for Reliable Information




1. ASSESSMENTS OF RADIOLOGICAL CONTAMINATION Surface survey

- Detailed measurements and mapping of ground surface deposition distribution of radionuclides
- Wide area radiation dose-rate distribution
 measurements and mapping using monitoring
 vehicles
- ◆ The results provides the source term for predictive models of future radioactive spread.






Cs-137 deposition distribution map





Dose-rate measurement at each mesh elements




Measurement using survey vehicles


1. ASSESSMENTS OF RADIOLOGICAL CONTAMINATION Aircraft radiation monitoring around Fukushima NPP1






1. ASSESSMENTS OF RADIOLOGICAL CONTAMINATION Aircraft radiation monitoring around Fukushima





2. DEMONSTRATION of DECONTAMINATION MEASURES School and kindergarten playground



- ◆ First aid: "Decrease the playground dose rate and store the removed soil in-situ."
- JAEA team;
 - ✓ performed precise dose rate measurements,
 - ✓ identified the cesium intrusion depth, and
 - ✓ estimated the safety of underground trench storage of the removed soil. .



- ◆ Contaminated surface soil of 5-cm thick was removed and put into trenches in a corner of the schoolyard.
- Dose rate significantly reduced by factors of 10 to 20;
 - ✓ School: (avg.) $2.5 \rightarrow 0.15 \,\mu\text{Sv/h}$ at 1 m^H
 - ✓ Kindergarten : (avg.) $2.8 \rightarrow 0.22 \mu Sv/h$ at 50 cm^H
- ◆ The results underlies the government, MEXT, announcement to apply the remove-and-trench work as a tentative dose reduction to Fukushima schools.

2. DEMONSTRATION of DECONTAMINATION MEASURES School swimming pool

- Not a few outdoor swimming pools still hold Cs rich water.
- The flocculation method applied for purification of water.
- Radioactive sludge was collected and stored at a temporary storage space.
- User-friendly handbook; "Guide for Decontaminating Swimming Pool at Schools" was published.
- Fostered a trustful relationship with school officials, municipality and residents through dialogue and decontamination works.





"Kizuna" (絆: bond) team and JAEA staff for school pool decontamination

2. DEMONSTRATION of DECONTAMINATION MEASURES Demonstration of decontamination measures for residential areas

Demonstration of Decontamination Technologies;

- ✓ review previous experiences,
- ✓ apply proven/improved/new technologies to the model sites,
- ✓ evaluate efficiency, cost, generation of waste, safety, and so on.
- ✓ establish "technologies catalogue"

Demonstration of Decontamination Methodology;

- ✓ propose brief approach and draft guideline
- ✓ extract points to be considered during decontamination at model sites
- ✓ update guideline


Demonstrations of decontamination measures at model sites;


- ✓ Model area-1: Areas including "Specific Spots recommended for Evacuation" (2 sites)
- ✓ Model area-2: Areas including "Deliberate Evacuation Area" & "Restricted Area" (12 municipalities)

2. DEMONSTRATION of DECONTAMINATION MEASURES

Demonstration of decontamination at model area-1

- City of Date and City of Minami Soma -






2. DEMONSTRATION of DECONTAMINATION MEASURES Demonstration of decontamination at model area-2

Demonstration of area decontamination

- Decontamination at model areas in Restricted / Deliberate Evacuation Areas in 12 municipalities
- The areas include;
 - ✓ various components to be decontaminated: forests, fields, residences, buildings, roads
 - ✓ various dose rate levels; high (> 100 mSv/y), intermediate (20 – 100), and low (5 – 20)
- Evaluation of <u>efficiency</u>, <u>generation of wastes</u>, <u>cost</u>, <u>safety</u>.

Demonstration of technologies


- ◆ Competition of improved/innovative decontamination technologies
 ✓ select 25 feasible and applicable proposals
- Demonstration at the site(s)
- Evaluation of <u>efficiency</u>, <u>generation of wastes</u>, <u>cost</u>, <u>safety</u>.



2. DEMONSTRATION of DECONTAMINATION MEASURES Temporary storage trench for removed contaminants



Temporary storage methods will be changed depending on radioactivity of removed contaminants and style of land utilization.



3. R&D for ENVIRONMENTAL RESTORATION

Monitoring system using an Autonomous Unmanned Helicopter (AUH)

Monitoring system using AUH






Air dose rate (1 m high) can be measured from an altitude of 30 m

Monitoring above rice paddy/forest



Monitoring above Shimo oguni area of Date city






3. R&D on ENVIRONMENTAL RESTORATION

Measurement of radiation distribution by Plastic **Scintillation Fibers (PSFs)**



- Two-dimensional measurement
- Rolling and contoured surface, due the bendable nature.
- ◆ Underwater surface such as brook bed and pond settlement, due to the waterproofness.








3. R&D on ENVIRONMENTAL RESTORATION Computer Simulation for Dose Reduction

The computer simulation helps planning of decontamination projects by providing information including effective decontamination measures, spatial priority, and waste generation.



4. COMMUNICATIONS and INSTRUCTIONS

Question-and-answer session on radiation and health

- ◆ JAEA technical staff are dispatched to Fukushima prefecture schools (from kindergartens to junior high schools) upon their request
- After briefings on radiation, JAEA staff members talk face-to-face with parents and teachers, answering their questions on radiation and its health effects.
- 132 sessions have been held since July, and a total of 142 sessions are scheduled as of December 4.






Briefing materials


4. COMMUNICATIONS and INSTRUCTIONS WBC measurement for Fukushima pref. residents

JAEA have measures internal exposure of people within the restricted area and deliberate evacuation area using the Whole Body Counter (WBC) in Tokai Laboratory

- ✓ About 100 persons are measured per day
- ✓ About 7,300 have been measured by last November, and a total of 8,000 persons are scheduled by the end of December, 2011.
- √ 15 minute-to-1 hour Q&A after measurement per person is welcomed



Measurement by Whole Body Counter



Energy spectrum measured

4. COMMUNICATIONS and INSTRUCTIONS

Dispatch of supervisors to training sessions on "Certified Decontamination Workers/Operators"

◆ JAEA dispatches its experts to official training course of decontamination works planned by Fukushima pref., as supervisors to ensuring safety and enhancing the skills of workers and operators engaging in decontamination works.

 Participants completed are certified by the governor of

Fukushima.

 3,000 workers and operators (equivalent to half of constructors in Fukushima) will be anticipated by the end of FY2011.





Completion certificate


Curriculum of training session

Day 1	Day 2	
Opening	5. Safety	
1. Overview of the accident	management during decontamination works	
2. Fundamental knowledge on radiation	6. Radiation effects on human health	
3. Radiation safety management	7. Demonstration and practice	
4. Decontamination method	8. Exam.	
	Closing	

Radiation survey (whole area to be remediated)








Model area in Minami Soma city

参考スライド Reference Slides

Radiation survey (whole area to be remediated)




Surface dose rate



Model area in Date city

Air dose rate [1 m]



Overview of approach

Preliminary planning for remediation

- Select demonstration site(s)
- Establish remediation goals and targets
- Estimate remediation sub-areas and inventories of contaminants
- List potentially appropriate remedial tools & methods

Radiation survey before remediation

- Detailed surface dose survey of the entire area
- Radiochemical assessment of relevant samples at appropriate locations
- Simple model assessment of inhabitant exposure

Establish remediation plan

- Integrate planning and site characterization data to develop improved site model
- Assess effectiveness of potential approaches to remediation for sub-areas on the basis of dose reduction, cost and safety
- Evaluate inventory of removed contaminants and interim storage and waste management requirements (conditioning, packaging, transportation, ...)
- Rank options and establish remediation plan (time schedule, remediation goals, uncertainty management processes, etc.)
- Workers safety

Apply remedial measures

- Stepwise implementation with monitoring procedures to check effectiveness of all remedial action
- Development of a complete inventory of all resultant materials in interim storage

Evaluate effectiveness of remedial measures

- Radiation survey after remediation, with associated sampling and analysis as required
- Examine remediation effectiveness in terms of radiation dose to critical groups
- Assess waste inventory, conditioning/packaging/transportation effectiveness and management options
- Record experience (including staff feedback)

Review
effectiveness
& establish
Remediation
Guidelines

Basic approach to establishing a remediation plan

Remedial measures

- Use well-tried, easy and practical measures
- > Ensure amounts of removed contaminants as low as practically achievable
- > Restrict use of water to the extent possible to avoid secondary contamination
- > Take measures to reduce environmental impact of remediation, if needed

Procedures

- ➤ Optimize remedial actions using a calculation tool to estimate dose rate reduction due to alternative approaches
- ➤ Generally implement remediation from higher to lower ground to reduce the risk of re-contamination
- An example of remedial actions for different target contaminants; Remediation of forest; restricted to a few meters tens meters from the edge of the forest
- ➤ In all cases, continuous radiation monitoring during actions to assess effectiveness and develop inventories of resultant waste


Remediation plan

Model area in Minami Soma city

Principal remediation methods for water tower Roof and drain pipe: Removal of dust (man power). wash and wipe (man power) STEP 1 · Field : Removal of fallen leaves and grass (man power), Removal of topsoil and soil dressing/compaction (man power, machine) Principal remediation methods for forest and grass- Fallen leaves: Removal of leaves (man power). STEP 2 •Grass: Removal of grass (man power, machine) ·Tal I tree: Trim Topsoil: Removal of topsoil (man power, machine). Soll dressing/compaction (machine) Principal remediation methods for bungalow Roof and drain pipe: Removal of dust (man power). wash and wipe (man power) STEP 3 -Field: Removal of fallen leaves and grass (man power), Removal of topsoil and soil dressing (man power machine) Principal remediation methods for grassfield Fallen leaves: Removal of leaves (man power) Grass: Removal of grass (man power, machine) STEP 4 ·Tall tree: Trim Topsoll: Removal of topsoll (man power, machine). Soli dressing/compaction (machine) Principal remediation methods for training house Roof and drain pipe: Removal of dust (man power), wash and wipe (man power) STEP 5 - Held: Removal of fallen leaves and grass (man power). Removal of topsoil and soil dressing (man power, machine) Principal remediation methods for horse riding area and parking area Fallen leaves: Removal of leaves (man power). Grass: Removal of grass (man power, machine) STEP 6 •Tal I tree: Trim Topsoil: Removal of topsoil (man power, machine). Soil dressing/compaction (machine) STEP 7 Principal remediation method for roads Pave road: blast (machine)



Trial of remedial actions for forest



Bird's-eye view of Trial Area

The trial area is divided into 3 zones.
Dimension of the zones are 10m wide and 10m length, respectively.









- > Following remedial items were examined in every remedial zone.
 - 1) weeding, 2) removal of fallen leaves, 3) removal of leaf mold.
- Finally, branches up to 4m height were cut off from the trees on forest boundary.
- ➤ Surface (at 1cm height) and ambient (at 1m height) dose rates were measured in the remedial zone and at forest boundary after carrying out every remedial item.

 $(\mu Sv/h)$

Dose rates after remedial items in each zone

remedial items Before remediation removal of fallen removal of leaf mold weeding leaves surface ambient surface ambient surface ambient surface ambient 3.4 2.5 3.5 2.8 1.6 1.8 Zone 1 2.5 2.5 3.3 2.7 3.2 2.5 2.4 2.3 1.7 1.7 Zone 2 Zone 3 3.1 2.5 3.2 2.4 2.5 2.2 1.6 1.4

After removal of leaf mold, surface and ambient dose rates were decreased 50% and from 30% to 40% lower than the condition before remediation, respectively.

Ambient dose rates at forest boundary after remedial actions of every zone and cutting off branches (µSv/h)

	before remediation	after zone 1	after zone 2	after zone 3	cutting off branches
forest boundary	2.4	2.2	2.3	2.4	2.1

Dose rates were not significantly decreased because of influence of contaminated materials around the trial area